



1900 Wellworth Ave. • Jackson, MI 49203
517-787-2100

Submittal Data

CMA1430SF-1

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Performance Data

Power supply Ph-V-Hz 208/230V~ 60Hz, 1Ph

Cooling

Capacity	Btu/h	30000
Total Load	A	8.95
EER	Btu/w	12.5
SEER	Btu/w	14.5
MIN. CIRCUIT AMPACITY	A	15
MAX.FUSE	A	25

Compressor Electrical

Model	ASH239DG-C8DU
Type	ROTARY
Brand	HIGHLY
Capacity	Btu/h 24072 (at 230V)
Input	W 2290 (at 230V)
Rated current(RLA)	A 10.2 (at 230V)
Coil Treatment	Silver

Fan Motor

Model	YDK-150-6CH F
Brand	CHIGO
Input	W 240
Capacitor	uF 5
Speed	r/min 800

Air Flow & Noise Level

Outdoor air flow	CFM	2647
Outdoor noise level	dB(A)	58

Controls

Thermostat type	Standard 24v Control
Connection wiring	18ga 2 Conductor



Min. Outdoor Ambient Temperature

Outdoor(cooling)	°F	65
------------------	----	----



System Operational Data

Design pressure	PSIG	540/300
Refrigerant oil		a68HES-H or equivalent
Oil charge	oz	16.23
Refrigerant type/charge	oz	R410A/3350g
Liquid side/ Vapor side	in	3/8-3/4
Max. length	ft	65.6
Max. height difference	ft	32.8

Dimensional Data

Dimension(W*D*H)	inch	41.1x17x31.1
Packing (W*D*H)	inch	44.1x19.1x35.43
Net/Gross weight	lbs.	143/154

CMA1430SF-1



Accessories

83907	Surge Protection
83916	Disconnect with internal surge
83335	60 amp Unfused Disconnect
93642	Wall Mount Bracket
93540	Condenser Pad

Dimensions

Model	CMA1430SF-1
A	41.1"
B	17.0"
C	31.1"
D	27.8"
E	15.5"