



Submittal Data

MODEL
REG-123R01

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 1Ph,230/208V-,60Hz

Cooling

Capacity	Btu/h	12,000/11,600
Input	W	1103/1066
Rated current	A	6.1/6.9
Max. Current	A	7.4
CEER	Btu/w	10.7

Heating

Capacity	Btu/h	11,000/8,500
RATED Input(Heater)	W	3460/3200
Rated current	A	14.5/15.7

Compressor Electrical


Model	KSM106N1VDZK	
Type	Rotary	
Brand	GMCC	
Capacity	Btu/h	12573
Input	W	925/935
Rated current(RLA)	A	4.48/4.12
Refrigerant type	oz	R32/14.46

Air flow & Noise level

Indoor air flow	CFM	543/482/426
Indoor noise level	dB(A)	61/58/55
Outdoor air flow	CFM	696/633/553
Outdoor noise level	dB(A)	67/64/61
Window Opening	Min/Max	26.8/36
	Width	
	Min Height	

Accessories

AS080 Window AC Support Bracket



Fan Motor

Model	YKTS-105-4-55L	
Input	W	142/127/112
Speed	RPM	1500/1380/1240

Dimensional Data

Dimension(W*D*H)	inch	21.46x18.98x14.65
Packing (W*D*H)	inch	23.07x21.93x16.93
Net/Gross weight	lbs.	71.65/78.26

SYSTEM DATA

Design pressure	PSIG	300/580
Thermostat type	Touchpad/Remote	
Application area (Cooling EPA)	450-550	

Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-20P

