



Submittal Data

MODEL
REG-183M

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 1Ph,230/208V-,60Hz

Cooling

Capacity	Btu/h	18500/18200
Input	W	1729/1701
Rated current	A	7.7/8.3
Max. Current	A	12.10
CEER	Btu/w	10.7
EER		10.7

Heating

Capacity	Btu/h	16000/13000
RATED Input(Heater)	W	4800/ 3925
Rated current	A	22.0 / 20.0

Compressor Electrical

Model	PA160M2A-3ETL
Type	Rotary
Brand	GMCC
Capacity	Btu/h 19073
Input	W 1325
Rated current(RLA)	A 5.80
Refrigerant type	oz R410A/28.92

Air flow & Noise level

Indoor air flow	CFM	446/388/329
Indoor noise level	dB(A)	60/57/54
Outdoor air flow	CFM	729./629/535
Outdoor noise level	dB(A)	66/63/59
Window Opening	Min/Max Width	26.5/40.5
	Min Height	18.5

Accessories

AS080	Window AC Support Bracket
NTN-2	Window AC Support Bracket



Fan Motor

Model	YKSS-150-6-3L(YSK150-6BH(B))
Input	W 225
Speed	RPM 1080/960/860

Dimensional Data

Dimension(W*D*H)	inch	23.6x25.4x17.9
Packing (W*D*H)	inch	26x30x19.7
Net/Gross weight	lbs.	118.4/133.4

SYSTEM DATA

Design pressure	PSIG	300/520
Thermostat type		Touchpad/Remote
Application area (Cooling EPA)		700-1000

Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-30P

