

RAH-123R 12,000 BTUH - Heat Pump

Date: _____

Job Name _____

Location: _____

Purchaser: _____

P.O. No.: _____

Engineer: _____

Architect: _____

Submitted To: _____

For: Reference Approval Construction

Submitted By: _____

Tag #: _____



SPECIFICATIONS

| | |
|--------------------------|---|
| Cooling Capacity BTUH | 11,200/11,800 |
| Approx. Sq. Ft. Cooling | 450-550 |
| EER | 9.9 |
| Power Supply | 208/230V 60Hz |
| Amps Cooling | 5.3/5.1 |
| Electric Heat Cap. BTUH | 10,300/12,500 |
| Electric Heat Amps | 16.0/14.6 |
| HP Heat Cap. BTUH | 9,900/10,200 |
| Heat Pump Amps | 5.3/5.1 |
| Heat Pump COP | 2.64 |
| Humidity Removal Pts/Hr | 3.17 |
| Fan Speeds Cool/Heat/Fan | 3/3/3 |
| dB Level (hi/med/low) | 72/70/68 |
| Ventilation Control | Yes |
| Fan Only | Yes |
| Air Delivery Max. CFM | 265 |
| Maximum Fuse Size | 20A |
| Power Cord | 20A Tee NEMA 6-20P |
| Slide-Out Chassis | Yes |
| Window Mounting Kit | Yes |
| Shipping Weight (lbs.) | 110 |
| Dimensions (in.) | Height 15.3 Width 22.6 Depth 23.6 |

FEATURES

- Electronic controls, wireless remote
- Automatic louver swing
- Thru-the-wall or window mount with support bracket included
- Cooling, heating, fan only, energy saver mode. and 24-hour timer
- Switches to supplemental electric heat at 40°F outside temperature



WARRANTY

1 Year Parts and Labor, 5 Year Sealed System

POWER CORD CONFIGURATIONS

