

START A DRAINPAN OFF RIGHT! Repair DON'T Replace

REPAIR:

Repair leaking drain pans without replacing equipment or entire units.

UPGRADE:

Apply during new installations to extend the life of your equipment. Put a stop to damage and corrosion and prevent future water damage.



ORANGE

For Professional Use Only KEEP AWAY FROM CHILDREN

EMERGENCY 1-800-255-3924 24 Hours www.highsidechem.com

HIGHSIDE CHEMICALS INC.

GULFPORT, MISSISSIPPI 39503





GHSIDE CHEMICALS INC. GULFPORT, MISSISSIPPI 39503 highsidechem.com • 800-359-5599



For Professional Use Only KEEP AWAY FROM CHILDREN EMERGENCY 1-800-255-3924 24 Hours www.highsidechem.com

ORAN

Cle rev

Cov duc tem ope

Pou (Yel onto prot read

Onc con rem

DOI PRO

**Tip full o or m are a

Allov hour, temp

**NO failur

GHSIDE CHEMICALS INC.

Turn off al



Orange Pan Potion[™] Instructions

Turn off all power to the system.

Remove panel of the air handler revealing drain pan, remove drain pan.

Clear drain pan of any debris, oils, etc. revealing a clean, dry surface.

Cover any penetrating holes or cracks with duct tape on external side of the pan for temporary support & plug up the drain pipe opening, prior to application.

Pour Part A (Red Resin) bottle into Part B (Yellow Hardener) bottle, screw cap back onto bottle and begin shaking. Shake product thoroughly until contents have reached a consistent "orange" color.

Once fully mixed, pour out ENTIRE contents into pan, some residual will remain.

DO NOT LEAVE EXCESSIVE AMOUNT OF PRODUCT IN BOTTLE

**Tip: Product is self-leveling. For a quicker, full coverage application, sit pan vertically or move pan around until desired results are achieved.

Allow product to cure for approximately 1 hour, results may vary depending on temperature and humidity.

**Note: Make sure to follow instructions, failure to fully mix product, can result in an improper application.

FOLLOW US ON SOCIAL MEDIA OR VISIT US ON THE WEB







