




SAFETY DATA SHEET

1. Identification

Product identifier	3-36® Multi-Purpose Lubricant & Corrosion Inhibitor
Other means of identification	
Product code	03004, 03005
Recommended use	Multi-purpose lubricant
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufactured or sold by:	
Company name	CRC Industries, Inc.
Address	885 Louis Dr. Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical Assistance	800-521-3168
Customer Service	800-272-4620
24-Hour Emergency (CHEMTREC)	800-424-9300 (US) 703-527-3887 (International)
Website	www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols Gases under pressure	Category 1 Compressed gas
Health hazards	Skin corrosion/irritation Specific target organ toxicity, single exposure Aspiration hazard	Category 2 Category 3 narcotic effects Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		

Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Wear protective gloves. Wash hands thoroughly after handling.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	60 - 70
Distillates (petroleum), Solvent-refined Heavy Paraffinic		64741-88-4	10 - 20
n-Butyl stearate		123-95-5	3 - 5
Carbon dioxide		124-38-9	1 - 3
Fatty Acids, C18-unsatd., Dimers		61788-89-4	1 - 3
Petrolatum		8009-03-8	1 - 3
d-Limonene		5989-27-5	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause drowsiness or dizziness. Irritant effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water. Water spray. Dry powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Components

Components	Type	Value	Form
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)	TWA	5 mg/m3	Respirable

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components

Components	Type	Value	Form
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	PEL	5000 ppm 5 mg/m3	Mist.

Petrolatum (CAS 8009-03-8)

PEL

2000 mg/m3
500 ppm
5 mg/m3

Mist.

ACGIH

Components

Components	Type	Value	Form
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)	STEL	10 mg/m3	Respirable
	TWA	5 mg/m3	Respirable

US. ACGIH Threshold Limit Values

Components

Components	Type	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	TWA	5000 ppm	
n-Butyl stearate (CAS 123-95-5)	TWA	5 mg/m3	Inhalable fraction.
Petrolatum (CAS 8009-03-8)	TWA	10 mg/m3	
	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components

Components	Type	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
	TWA	30000 ppm 9000 mg/m3 5000 ppm	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	100 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	STEL	10 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Mist.
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
d-Limonene (CAS 5989-27-5)	TWA	165.5 mg/m3 30 ppm

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear eye/face protection. Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as neoprene or nitrile.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Blue green.
Odor	Pleasant.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-72.4 °F (-58 °C) estimated
Initial boiling point and boiling range	380 °F (193.3 °C) estimated
Flash point	192 °F (88.9 °C) Tag Closed Cup
Evaporation rate	Slow
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	5.5 % estimated
Vapor pressure	1431 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.84 estimated
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	456.8 °F (236 °C) estimated
Decomposition temperature	Not available.

Viscosity (kinematic)	Not available.
Percent volatile	88.6 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritant effects.
---	--

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects.
-----------------------	---

Product	Species	Test Results
3-36® Multi-Purpose Lubricant & Corrosion Inhibitor		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2818.8381 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	116.664 mg/l estimated
<i>Oral</i>		
LD50	Rat	6740.1777 mg/kg estimated
Subchronic		
<i>Oral</i>		
LD50	Rat	1166.0905 g/kg, 14 days estimated

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
d-Limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Narcotic effects.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
3-36® Multi-Purpose Lubricant & Corrosion Inhibitor		
<i>Acute</i>		
Fish	LC50	Fish 4916.4028 ppm, 96 hours estimated
Components	Species	Test Results
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)		
<i>Aquatic</i>		
<i>Acute</i>		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 2.2 mg/l, 96 hours
d-Limonene (CAS 5989-27-5)		
<i>Aquatic</i>		
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>) 69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 0.619 - 0.796 mg/l, 96 hours
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)		
<i>Acute</i>		
Crustacea	NOEL	Daphnia 1000 mg/l, 48 hours loading rate WAF
Fish	NOEL	Fish 1000 mg/l, 96 hours loading rate WAF

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

d-Limonene	4.232
Fatty Acids, C18-unsatd., Dimers	1 - 2.5, logKow

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Hazardous waste code Not regulated.

Contaminated packaging Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Not available.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	2L

Special precautions for user Not available.

Other information

Passenger and cargo aircraft Allowed.

Cargo aircraft only Allowed.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, LIMITED QUANTITY

Transport hazard class(es)

Class 2

Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS F-D, S-U

Special precautions for user Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes

Hazard categories Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. New Jersey RTK - Substances: Listed substance

Carbon dioxide (CAS 124-38-9)

US. Massachusetts RTK - Substance List

Carbon dioxide (CAS 124-38-9)

US. Pennsylvania RTK - Hazardous Substances

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) 97.5 %

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states.

VOC content (CA) 0 %

VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-11-2013
Prepared by	Allison Cho
Version #	01
Further information	CRC # 510F
HMIS® ratings	Health: 1 Flammability: 3 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 3 Instability: 0
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.